

# 3D LASER SCANNER LPX-600



## 3D Scanning at the Touch of a Button

### Amazingly Easy To Use — LPX-600 laser scanner generates 3D digital data for 3D CAD/CG

Roland's LPX-600 makes 3D laser scanning easier than ever. With the simplicity of operation similar to a standard 2D scanner, you can now quickly and accurately create digital data from an object for 3D CAD/CG applications. The LPX-600 sets up easily for professional results right out of the box. No special training is required.

- Includes Roland LPX EZ Studio scanning software.
- Features USB connection for easy setup.
- Benchtop size and quiet operation make the LPX-600 ideal for any office environment.

#### Scan your object in three easy steps



**1** Position your object on the LPX-600 work table



**2** Press the 'Preview' button to confirm scanning time



**3** Press the 'Scan' button to begin scanning




# 3D LASER SCANNER LPX-600



## Easy-to-use Roland LPX EZ Studio scanning software included


Roland LPX EZ Studio scanning software controls the entire process from the initial scan to the creation of 3D CAD/CG data in a range of file formats including STL (Standard Tessellated Language, industry standard 3D CAD), GSF (Geometry Systems native file format) and 3DM (Rhino format). EZ Studio automatically eliminates extra polygons and fills holes for smooth, continuous surfaces.\*

\* The ability to fill holes automatically depends on the shape of the object and whether the laser can reach all sides including front and back.



## Large working area and high-quality scanning as precise as 0.2mm (0.008") scanning-pitch

The LPX-600 allows you to scan a wide variety of objects as large as 254mm (10") in diameter and 406.4 (16") mm in height. The laser scans a maximum of 20 surfaces at right angles at a scanning pitch as fine as 0.2mm (0.008"). Once scanning starts, the laser travels vertically up the rotating object to generate a 3D file.



## A choice of two powerful packages for advanced users — Dr. PICZA 3 Scanning Software included or Pixform Pro Surface Software available as an option

The LPX-600 operates with either of two powerful software packages for advanced applications. Dr. PICZA 3 allows users to scan a designated area of an object by specifying the height, width, offset distance from the center, and the scanning angle required. In addition, it exports poly-line or point scanning data as 3D CAD data.

The LPX-600 can also be purchased with optional Pixform Pro software which supports robust polygon to NURB surface conversion and features numerous editing functions. With Pixform Pro, users can merge data scanned at different angles into one continuous surface, free of holes and undercuts. It can also smooth polygon data for even surface editing, curve generation and Boolean operations. Pixform Pro supports a wide array of 3D CAD/CG software as well.



● Dr. PICZA 3



● Pixform Pro

## Specifications

LPX-600			
<b>Table size</b>	Diameter 254mm (10 in.)	<b>Operating speed</b>	Table rotation speed: 9rpm, head rotation speed: 4.48rpm, maximum head movement speed: 37mm/sec.
<b>Maximum scanning area</b>	Plane scanning: Width 254mm (10 in.), height 406.4mm (16 in.) Rotary scanning: Diameter 254mm (10 in.), height 406.4mm (16 in.)	<b>Interface</b>	USB (compliant with Universal Serial Bus Specification Revision 1.1)
<b>Scanning pitch</b>	Plane scanning: width direction 0.2 to 254mm, height direction 0.2 to 406.4mm. Rotary scanning: circumference 0.18 to 3.6 degrees, height direction 0.2 to 406.4mm	<b>Power supply</b>	Dedicated AC adapter Input: AC 100 to 240 V ±10% 50/60 Hz 1.7A, Output: DC 19V, 2.1A
<b>Repeat accuracy</b>	±0.05mm (This figure reflects standard scanning conditions established by Roland DG.)	<b>Power consumption</b>	Approx. 20W (including AC adapter)
<b>Maximum table load weight</b>	5kg (11 lbs.)	<b>Dimensions</b>	630 [W] x 506 [D] x 761 [H] mm (24-13/16 [W] x 19-15/16 [D] x 29-15/16 [H] in.)
<b>Laser</b>	Wavelength: 645 to 660nm Maximum output: less than 0.39μW (maximum output of the laser light emitted inside housing is 0.1mW)	<b>Weight</b>	63kg (139 lbs.)
<b>Sensor</b>	Noncontact laser sensor	<b>Environment</b>	Temperature: 10 to 40°C (50 to 104°F) (25°C (77°F) or more recommended) Humidity: 35 to 80% (no condensation)
<b>Scanning method</b>	Spot-beam triangulation	<b>Included items</b>	AC adapter, power cord, AC adapter holder, cable clamps, USB cable, CD-ROM, clay, user's manual, scanning software

## System Requirements for Included Software

<b>Operating system</b>	Windows XP/2000/Me/98 SE (Second Edition)
<b>CPU</b>	Pentium 4 processor or better recommended
<b>Memory</b>	512MB or more recommended
<b>Free hard-disk space required for installation</b>	Dr. PICZA 3: 20MB or more 3D Editor: 10MB or more
<b>Display</b>	800 x 600 resolution and 16 bit color (High color) or more recommended. OpenGL-compatible accelerator board recommended.

## System Requirements for USB Connection

<b>Operating system</b>	Windows XP/2000/Me/98 SE (Second Edition)
<b>Computer</b>	1) Computers preinstalled with Windows 98/Me/2000/XP at the time of purchase (This includes such computers later upgraded to Windows Me/2000/XP) 2) Computers on which USB operation is assured by the manufacturer of computers
<b>USB Cable</b>	Use the included USB cable. Do not use a USB hub or the like.

## Options

Item	Description
Pixform Pro	Surface Software for LPX-600

## ISO 14001 and ISO 9001:2000 Certified

Roland pursues both environmental protection and continuous quality improvement. Under the philosophy of preserving the environment and human health, Roland DG is actively working to abolish organic solvents in production, to reduce and recycle waste, to reduce power use, and to purchase recycled products. Roland DG constantly strives to provide the most highly reliable products available.



Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Three-dimensional shapes may be protected under copyright. Customers are responsible for observing laws and ordinances when scanning. All trademarks are the property of their respective owners.



**Roland**

AUTHORIZED DEALER:

Printed in Japan. RDG-416003699 '05 NOV. A-4 G-S

**YARHAMVILLE PTY LTD**  
1300 136 359